(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

10/506884

(43) International Publication Date
12 September 2003 (12.09.2003)

PCT

(10) International Publication Number
WO 03/075213 A2

(51) International Patent Classification[7]: G06K 11/16, 11/18

(21) International Application Number: PCT/GB02/05247

(22) International Filing Date:
22 November 2002 (22.11.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0205116.7	5 March 2002 (05.03.2002)	GB
0209372.2	24 April 2002 (24.04.2002)	GB
PCT/GB02/02387	21 May 2002 (21.05.2002)	GB
0212699.3	31 May 2002 (31.05.2002)	GB

(71) Applicant *(for all designated States except US)*: **SYNAPTICS (UK) LIMITED** [GB/GB]; 7340 Cambridge Research Park, Ely Road, Waterbeach, Cambridgeshire CB5 9TB (GB).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: **ELY, David, Thomas, Eliot** [GB/GB]; Synaptics (UK) Limited, 7340 Cambridge Research Park, Ely Road, Waterbeach, Cambridgeshire CB5 9TB (GB). **MCCAUGHAN, Gareth, John** [GB/GB]; Synaptics (UK) Limited, 7340 Cambridge Research Park, Ely Road, Waterbeach, Cambridgeshire CB5 9TB (GB). **FOOTE, Geoffrey** [GB/GB]; Synaptics (UK) Limited, 7340 Cambridge Research Park, Ely Road, Waterbeach, Cambridgeshire CB5 9TB (GB).

(74) Agents: **BERESFORD, Keith, Denis, Lewis** et al.; Beresford & Co., 2-5 Warwick Court, High Holborn, London WC1R 5DH (GB).

(81) Designated States *(national)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: POSITION SENSOR



(57) Abstract: A low cost x-y digitising system is described for use in consumer electronic devices, such as portable digital assistants, mobile telephones, web browsers and the like. The digitiser includes a resonant stylus, an excitation winding for energising the resonant stylus and a set of sensor windings for sensing the signal generated by the stylus, from which the x-y position of the stylus is determined. A novel stylus design is described together with novel digitiser windings and novel excitation and processing circuitry.

WO 03/075213 A2